DRILLING & FISHING TOOLS AND BHA INSPECTION REPORT

Aberdeen Technical Services
www.aberdeents-iq.com
Iraq –Basra – AlBarjisia
Tel: +964 7833334444 +964 7822222633
Emails:
akader@aberdeents.com
inspection@aberdeents-iq.com

CUSTOMER:	AL-JOHD	RIG NO.:	--	DEPARTMENT:	directional drilling services	PAGE NO.:	Page 1 of 1	REPORT NO.:	ATS-JOH-24-04-3173-012
LOCATION:	Aberdeen Yard	REF NO.:	--	PO/FIRE NO.:	--	JOB NO.:	ATS-JOH-24-04-3173	DATE:	02-May-2024

INSPECTION / SERVICES PROVIDED				INSPECTION TOOL USED			CONSUMEBALES USED		
SPECIFICATION		SCOPE OF WORK		TOOL	SERIAL NO.	CAL. DUE DATA	CONSUMEBALES	BATCH NO.	EXPIRY
■	DS 1 Volume 4,Fifth Edition	■	VISUAL BODY	■ AC YOKE	201504044	04-Jul-2024	WHITE CONTRAST (FLUXO 4)	L230523	23/05/2028
	API Specs 7	■	MAGNETIC PARTICLE INSPECTION (MPI)	■ LIFTING BLOCK	1657	04-Jul-2024	BLACK MAGNETIC INK (FLUXO 3)	L230125	25/01/2028
■	CUSTOMER SPECIFICATION		DYE PENETRANT INSPECTION (DPI)	■ BLACK LIGHT	87611	04-Jul-2024	■ FLUORESCENT MAGNETIC INK (FLUXO 4)	L221115	15/11/2027
	NS2	■	DIMENSIONAL 3	■ INTENSITY METER	-	-	PENETRANT	L220902	2/9/2027
	API RP 7G-2	■	VISUAL CONNECTION	■ DC COIL	026	04-Jul-2024	DEVELOPER	L221010	10/10/2027
	API 5CT		BORESCOPE	■ COMPARATOR BLOCK	-	-	CLEANER	L230103	23/01/2028

EQUIPMENT DESCRIPTION:	8'' DRILLING JAR	SERIAL NO.:	CW-1423633-2	BLADE AREA OD	--	MATERIAL:	■ FERRO-MAGNETIC	NON-MAGNETIC

TOOL SPECIFICATION			CONNECTIONS : DIMENSIONAL DATA (INCHES) & CONDITIONS																										
				CONNECTION END AREA													CONNECTION END AREA												
SERIAL No.	DESCRIPTION	LENGTH INCHES	ID	BOX or PIN	CONNECTION Type	OD	BEVEL DIA	COUNTER BORE		BOREBACK		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION	BOX or PIN	CONNECTION Type	OD	BEVEL DIA	COUNTER BORE		FLOAT BORE		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION
								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH			
CW-1460125-8	SPLINED MANDREL	84	2 13/16	BOX	6 5/8 REG	8 1/8	7 17/32	6 1/16	21/32	5 9/32	8 3/4	-	-	-	21 3/16	OK	PIN	SPL	-	-	-	-	-	-	-	-	-	-	OK
CW-735251	SPLINED HOUSING	30 15/16	6 1/16	PIN	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK	PIN	SPL	8	-	-	-	-	-	-	-	-	-	OK
CW-03	KNOCKER HOUSING	30 7/8	-	BOX	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK	BOX	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK
CW1425523-1	HYDRAULIC HOUSING	35 1/16	-	BOX	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK	PIN	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK
CW-02	KNOCKER MANDREL	37 1/2	2 13/16	BOX	SPL	5 7/8	-	-	-	-	-	-	-	-	1 1/4	OK	PIN	SPL	4	-	-	-	-	-	-	-	-	-	OK
CW-04	LATCH HOUSING	52 13/16	4 7/16	BOX	SPL	8 1/16	-	-	-	-	-	-	-	-	36 1/2	OK	PIN	SPL	8 1/16	-	-	-	-	-	-	-	-	5 1/2	OK
CW1460126-6	BOTTOM SUB	35 1/2	2 25/32	PIN	6 5/8 REG	8 1/8	7 1/2	-	-	-	-	5 13/32	3/4	4 31/32	61 3/8	OK	PIN	SPL	8	-	-	-	-	-	-	-	-	4 3/8	OK
AECW-1352646-3	LATCH MANDREL	68 1/2	2 13/16	BOX	SPL	5 1/2	-	-	-	-	-	-	-	-	-	OK	PIN	SPL	4 1/4	-	-	-	-	-	-	-	-	-	OK
CW-05	SAFETY NUT	2 3/8	-	BOX	SPL	4 1/2	-	-	-	-	-	-	-	-	-	OK	-	-	-	-	-	-	-	-	-	-	-	-	-
CW-01	SEAL HOUSING	12	-	BOX	SPL	8 1/8	-	-	-	-	-	-	-	-	-	OK	-	-	-	-	-	-	-	-	-	-	-	-	-

ABBREVATIONS:												CONNECTIONS :				SUMMARY:	
DT	DAMAGED THREAD	PT	PITTED THREAD	GT	GALLED THREAD	CT	CORRODED THREAD	P.RG	PITTIED RELIEF GROOVE	DS	DAMAGED SEAL	BOX		PIN		Acceptable:	10
GS	GALLED SEAL	C.RG	CORRODED RELIEF GROOV	CS	CORRODED SEAL	PS	PITTED SEAL	CRK	CRACK	DF	DIMENSIONALLY FAILED		CW		CW	Rejected:	0
WT	WORN THREAD	RF	RE-FACED	WOT	WASH OUT THREAD	CBB	CORRODED BOREBACK	CFP	CORRODED FLOAT BORE	DFB	DAMAGED FLOAT BORE		SP		SP	Scrap:	0
SW	SWELLED	SQ	SQUEEZE CONNECTION	MFC	MANUFACTURER CONNECTION	P.BB	PITTED BORE BACK						SUL		SUL	Qty Insp.:	10

COMMENTS:	THE ABOVE-MENTIONED ITEM WAS INSPECTED (FULL BODY) AND FOUND "ACCEPTED" AT THE TIME OF INSPECTION.	NAME OF INSPECTOR:	ARAM DLAWAR	SIGNATURE:	Reviewed by:	Hasan Omran	STAMP & SIGNATURE:
		QUALIFICATION:	ASNT NDT LEVEL-ll		QUALIFICATION:	ASNT NDT LEVEL-ll Inspection Supervisor	

ATS-BHA-F-24-001