



# DRILLING / BHA / AND SPECIALITY TOOLS INSPECTION REPORT

**Aberdeen Technical Services**  
[www.aberdeents-iq.com](http://www.aberdeents-iq.com)  
 Iraq –Basra – AlBarjisia  
 Tel: +964 7833334444 +964 7822222633  
 Emails:  
[akader@aberdeents.com](mailto:akader@aberdeents.com)  
[inspection@aberdeents-iq.com](mailto:inspection@aberdeents-iq.com)

<b>CUSTOMER:</b>	Hilong Oil Services & Engineering	<b>RIG NO.:</b>	HL - 100	<b>DEPARTMENT:</b>	--	<b>PAGE NO.:</b>	Page 1 of 1	<b>REPORT NO.:</b>	ATS-08-24-4132-008
<b>LOCATION:</b>	Northern Rumila / R026	<b>REF NO.:</b>	--	<b>PO/FIRE NO.:</b>	--	<b>JOB NO.:</b>	ATS-08-24-4132	<b>DATE:</b>	28/8/2024

INSPECTION / SERVICES PROVIDED		INSPECTION TOOL USED				CONSUMEBALES USED			
SPECIFICATION	SCOPE OF WORK (CAT: 3-5)	TOOL	SERIAL NO.	CAL. DUE DATA	CONSUMEBALES	BATCH NO.	EXPIRY		
■ DS 1 Volume 3,Fifth Edition	■ VISUAL BODY	■ AC YOKE	201504044	27-Dec-2024	WHITE CONTRAST (FLUXO 4)	L230523	23/05/2028		
■ API Specs 7	■ MAGNETIC PARTICLE INSPECTION (MPI)	■ LIFTING BLOCK	1657	27-Dec-2024	BLACK MAGNETIC INK (FLUXO 3)	L230125	25/01/2028		
■ CUSTOMER SPECIFICATION	■ DYE PENETRANT INSPECTION (DPI)	■ BLACK LIGHT	87611	27-Dec-2024	■ FLUORESCENT MAGNETIC INK (FLUXO 4)	L221115	15/11/2027		
■ NS2	■ DIMENSIONAL 3	■ INTENSITY METER	1965921	27-Dec-2024	■ PENETRANT	L220902	2/9/2027		
■ API RP 7G-2	■ VISUAL CONNECTION	■ DC COIL	026	27-Dec-2024	■ DEVELOPER	L221010	10/10/2027		
■ API SCT	■ BORESCOPE	■ COMPARATOR BLOCK	-	-	■ CLEANER	L230103	23/01/2028		

<b>EQUIPMENT DESCRIPTION:</b>	FOSV SUB	<b>SERIAL NO.:</b>	071808829	<b>BLADE AREA OD</b>	--	<b>MATERIAL:</b>	■ FERRO-MAGNETIC	■ NON-MAGNETIC
-------------------------------	----------	--------------------	-----------	----------------------	----	------------------	------------------	----------------

TOOL SPECIFICATION				CONNECTIONS : DIMENSIONAL DATA ( INCHES ) & CONDITIONS																											
SERIAL No.	DESCRIPTION	LENGTH (INCHES)	ID	CONNECTION END AREA												CONNECTION END AREA															
				BOX or PIN	CONNECTION TYPE	OD	BEVEL DIA	COUNTER BORE		BOREBACK		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION	BOX or PIN	CONNECTION TYPE	OD	BEVEL DIA	COUNTER BORE		FLOAT BORE		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION		
								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH					
071808829	FOSV SUB	17 3/4	1 3/4	BOX	3 1/2 EUE	4 1/2	-	-	-	-	-	-	-	-	-	14	ok	PIN	3 1/2 EUE	4 1/2	-	-	-	-	-	-	-	-	-	-	ok

ABBREVIATIONS:												CONNECTIONS :			SUMMARY:	
DT	DAMAGED THREAD	PT	PITTED THREAD	GT	GALLED THREAD	CT	CORRODED THREAD	P.RG	PITTED RELIEF GROOVE	DS	DAMAGED SEAL	BOX	PIN	Acceptable:	1	
GS	GALLED SEAL	C.RG	CORRODED RELIEF GROOV	CS	CORRODED SEAL	PS	PITTED SEAL	CRK	CRACK	DF	DIMENSIONALLY FAILED	CW	CW	Rejected:	0	
WT	WORN THREAD	RF	RE-FACED	WOT	WASH OUT THREAD	CBB	CORRODED BOREBACK	CFP	CORRODED FLOAT BORE	DFB	DAMAGED FLOAT BORE	SP	SP	Scrap:	0	
SW	SWELLED	SQ	SQUEEZE CONNECTION	MFC	MANUFACTURER CONNECTION	P.BB	PITTED BORE BACK	M.CH	MISSING CHROME			SUL	SUL	Qty Insp.:	1	

<b>COMMENTS:</b>	THE ABOVE-MENTIONED ITEM WAS INSPECTED (FULL BODY) AND FOUND "ACCEPTED" AT THE TIME OF INSPECTION.	<b>NAME OF INSPECTOR:</b>	ARAM DLAWAR	<b>SIGNATURE:</b>		<b>Reviewed by:</b>	Hasan Omran	<b>STAMP &amp; SIGNATURE:</b>	
	<b>QUALIFICATION:</b>	ASNT NDT LEVEL-II	<b>QUALIFICATION:</b>			ASNT NDT LEVEL-II	Inspection Supervisor		

