



CERTIFICATE OF CONFORMITY (COC)

THIS IS TO CERTIFY THAT: The **Gate Valve** described hereby has been re-certified (Major Surveyed) based on the requirements of the **relative standards and OEM Requirements**, the Gate valve has been experienced the described below inspections/tests/witnesses and all the results found **accepted** as per the standards / OEM acceptance criteria, therefore the mentioned-below Gate valve has been considered **safe** to continue in service.

Certificate No.: ATS-NESR-WT-2025-04

Client: [National Energy Services Reunited Corp \(NESR\) – Iraq Branch](#)

Department: Well Testing (WT)

Location: Iraq - Basra – NESR Base

Major Survey Date: May/2025

Equipment Description: **Gate Valve 3 1/8" – 5 K**

Serial Number: **IO00116885-44**

Model / Date of MFG: WOM M200 / 2019

OEM: WORLDWIDE OILFIELD MACHINE (WOM)

Weight: approx. 353 lbs

Conform with Relative Standard: [ASME B31.1:2024](#), [ASTM E709-21](#), [ASTM E797-21](#), [API Spec 6A:2024](#), [ASME BPVC Section V:2023](#), [ASTM E1444-22](#), [ASTM E10-23](#), [ASTM E110-23](#), [ASME Sec VIII Div 2:2023](#).

Unit: Gate Valve – 3 1/8" – 5 K

Description:

Gate Valve – 3 1/8" – 5K consists of:

- Valve Body
- Valve Gate
- Seals
- Packing Stem
- Seal Assembly
- Bonnet Studs, 1-1/8" Dia, 7.32" Length, 8 Studs with 8 Nuts
- Flange Bolts, 1" Dia, 7.32" Length, 16 Bolts with 32 Nuts
- Stem
- Bonnet

Remarks:

The following Tests/ Inspections/Witnesses have been carried out on the above-mentioned Gate Valve Assembly:

- Visual Inspection & Thorough Examination
- Magnetic Particles Inspection (MPI)
- Hardness Testing (HB)
- Witnessing of Pressure Tests / Body Test (Low: 300 psi / 05 Minutes, High: up to 7500 Psi / 10 Minutes)
- Ultrasonic Thickness Measuring (UTM)

Certified By: Eng. Hasan Omran

Signature:

Date: 30-May-2025



Approved By: Eng. Majd Dayoub

Signature:

Date: 31-May-2025

Next Re-certification Date: May-2030

