DRILLING & FISHING TOOLS AND BHA INSPECTION REPORT

Aberdeen Technical Services
www.aberdeents-iq.com
Iraq –Basra – AlBarjisia
Tel: +964 7833334444 +964 7822222633
Emails:
akader@aberdeents.com
inspection@aberdeents-iq.com

CUSTOMER:	AL-JUHUD	RIG NO.:	--	DEPARTMENT:	Directional drilling services	PAGE NO.:	Page 1 of 1	REPORT NO.:	ATS-5273-01-2026-003
LOCATION:	Aberdeen Yard	REF NO.:	--	PO/FIRE NO.:	--	JOB NO.:	ATS-5273-01-2026	DATE:	12-Jan-2026

INSPECTION / SERVICES PROVIDED				INSPECTION TOOL USED				CONSUMEBALES USED			
SPECIFICATION		SCOPE OF WORK		TOOL		SERIAL NO.	CAL. DUE DATA	CONSUMEBALES		BATCH NO.	EXPIRY
■	DS 1 Volume 4,Fifth Edition	■	VISUAL BODY	■	AC YOKE	201504044	03-Jun-2026		WHITE CONTRAST (FLUXO 4)	L230523	23/05/2028
	API Specs 7	■	MAGNETIC PARTICLE INSPECTION (MPI)	■	LIFTING BLOCK	1657	03-Jun-2026		BLACK MAGNETIC INK (FLUXO 3)	L230125	25/01/2028
■	CUSTOMER SPECIFICATION		DYE PENETRANT INSPECTION (DPI)	■	BLACK LIGHT	87611	03-Jun-2026	■	FLUORESCENT MAGNETIC INK (FLUXO 4)	L221115	15/11/2027
	NS2	■	DIMENSIONAL 3	■	INTENSITY METER	1965921	03-Jun-2026		PENETRANT	L220902	2/9/2027
	API RP 7G-2	■	VISUAL CONNECTION	■	DC COIL	026	03-Jun-2026		DEVELOPER	L221010	10/10/2027
	API 5CT		BORESCOPE	■	COMPARATOR BLOCK	ATS-CB-01	-		CLEANER	L230103	23/01/2028

EQUIPMENT DESCRIPTION:	4-3/4" DRILLING JAR	SERIAL NO.:	MHJ 47512	BLADE AREA OD	--	MATERIAL:	■ FERRO-MAGNETIC	NON-MAGNETIC

TOOL SPECIFICATION			CONNECTIONS : DIMENSIONAL DATA (INCHES) & CONDITIONS																										
				CONNECTION END AREA													CONNECTION END AREA												
SERIAL No.	DESCRIPTION	LENGTH INCHES	ID	BOX or PIN	CONNECTION Type	OD	BEVEL DIA	COUNTER BORE		BOREBACK		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION	BOX or PIN	CONNECTION Type	OD	BEVEL DIA	COUNTER BORE		FLOAT BORE		RELIEF GROOVE		PIN LENGTH	TONG SPACE	CONDITION
								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH								DIA	DEPTH	DIA	LENGTH	DIA	WIDTH			
MHJ47512	4-3/4" Drilling Jar	353-1/2"	2-1/4"	BOX	NC 38	4-13/16"	4-5/8"	4-1/16"	5/8"	3-15/32"	7-1/4"	-	-	-	20-3/8"	OK	PIN	NC 38	4-13/16"	4-5/8"	-	-	-	-	3-1/2"	3/4"	3-15/16"	9-1/8"	OK

ABBREVATIONS:												CONNECTIONS :				SUMMARY:	
DT	DAMAGED THREAD	PT	PITTED THREAD	GT	GALLED THREAD	CT	CORRODED THREAD	P.RG	PITTIED RELIEF GROOVE	DS	DAMAGED SEAL	BOX	PIN			Acceptable:	1
GS	GALLED SEAL	C.RG	CORRODED RELIEF GROOV	CS	CORRODED SEAL	PS	PITTED SEAL	CRK	CRACK	DF	DIMENSIONALLY FAILED	CW	CW			Rejected:	0
WT	WORN THREAD	RF	RE-FACED	WOT	WASH OUT THREAD	CBB	CORRODED BOREBACK	CFP	CORRODED FLOAT BORE	DFB	DAMAGED FLOAT BORE	SP	SP			Scrap:	0
SW	SWELLED	SQ	SQUEEZE CONNECTION	MFC	MANUFACTURER CONNECTION	P.BB	PITTED BORE BACK	M.CH	MISSING CHROME			SUL	SUL			Qty Insp.:	1

COMMENTS:	THE ABOVE-MENTIONED ITEM WAS INSPECTED (ENDS ONLY) AND FOUND "ACCEPTED" AT THE TIME OF INSPECTION.	NAME OF INSPECTOR:	TAYYAB ABBASI	SIGNATURE:	Reviewed by:	HASAN OMRAN	STAMP & SIGNATURE:
		QUALIFICATION:	ASNT NDT LEVEL-II		QUALIFICATION:	ASNT NDT LEVEL-II Inspection Supervisor	

ATS-BHA-F-24-001